

FOUR
STROKE

BFT250A



Exceed the European
Union emission standards.



California C.A.R.B.
three star rating
for ultra-low emissions.

FOUR STROKE

Specifications

Type		Four Stroke EFI
Maximum output	KW (PS)	183.9 (250)
Maximum operating range	rpm	5300-6300
Fuel consumption at W.O.T	L/Hr (gal/Hr)	82.7 (21.88)
Number of cylinder		6
Bore x Stroke	mm (in)	89 x 96 (3.50 x 3.78)
Displacement	cc (Cu in)	3583 (218.6)
Engine lubrication system		Trochoid pump
Starting system		Electric starter
Spark plug		ZFR6K-11 (NGK)
Ignition timing	degree	0° ±2° at 650 min ⁻¹ (rpm) B.T.D.C
Alternator output		12V, 60A
Engine oil		API Standard (SG, SH, SJ) SAE 10W-30
Engine oil capacity	L (gal)	7.8 (2.1) w/ Filter change
Fuel tank capacity	L (gal)	Option 25 (6.6)
Speed control		Remote Control
Gear reduction ratio		2.00 : 1
Emission Compliance		EU & EPA & CARB 3-Star

FOUR STROKE

Specifications and descriptions are subject to change without notice.

Standard & Optional Equipments

Type	X
Electric Starter	●
Engine Stop Switch Lanyard	●
Alternator	●
Rectifier	●
Power Trim & Tilt	●
Transom	25
Propeller	○
Analog Tachometer	○
Analog Trim Meter	○
Remote Control Box	○
25L (6.6 Gal) Plastic Fuel Tank	○
Tool Kit	●
Spare Spark Plugs	●
Owners Manual	●

● Standard ○ Optional

FOUR STROKE



6-Cylinder



PGM-FI®



BLAST®
SYSTEM



ECOmo®



Variable Valve
Timing and Lift
Control



Alternator



Charging System



Thermostat



Power Trim
& Tilt



Diagnostics



Over-Heat
Buzzer



Tohatsu Onboard
Communication
System