

FOUR
STROKE

MFS40A



Exceed the European
Union emission standards.



California C.A.R.B.
three star rating
for ultra-low emissions.

FOUR
STROKE

Specifications

Type		Four Stroke EFI
Maximum output	KW (PS)	29.4 (40)
Maximum operating range	r/min	5000-6000
Fuel consumption at W.O.T	L/Hr (gal/Hr)	13.7 (3.62)
Number of cylinder		3
Bore x Stroke	mm (in)	70 X 75 (2.75 X 2.95)
Displacement	ml (Cu in)	866 (52.84)
Engine lubrication system		Trochoid pump
Starting system		Electric starter
Spark plug		NGK DCPR6E
Ignition timing		Electronically advanced
Alternator output		12V 252W 21A
Engine oil		Tohatsu 4-Stroke Engine Oil
Engine oil capacity	L (qt)	2.4 (0.63) w/Filter change
Fuel tank capacity	L (gal)	25 (6.6)
Speed control		Multi Function Tiller Handle or Remote Control
Gear reduction ratio		2.08 (13:27)
Emission Compliance		EU & EPA & CARB 3-Star

FOUR STROKE

Specifications and descriptions are subject to change without notice.

Standard & Optional Equipments

Type	ETS/L	EGL
Electric Starter	●	●
Decompression Release	●	●
Engine Stop Switch Lanyard	●	●
Alternator	●	●
Rectifier	●	●
Power Trim & Tilt	●	-
Gas Assist Tilt	-	●
Transom	15/20	20
Propeller	●	●
Analog Tachometer	○	○
Analog Trim Meter	○	○
Remote Control Box	○	○
Multi Function Tiller Handle	○	○
25L (6.6 Gal) Plastic Fuel Tank	●	●
Tool Kit	●	●
Emergency Starter Rope	●	●
Spare Spark Plug	●	●
Owners Manual	●	●

● Standard ○ Optional



3-Cylinder



Electronic Fuel Injection



Low Fuel Consumption



Alternator



Charging System



Thermostat



Throttle Friction




Simple Steering Friction Lever



Power Trim & Tilt



Gas Assist Tilt



Trolling Speed Control



Diagnostics



Multifunctional Tachometer



Over-Heat Buzzer



High Solid Paint Coating



Tilt Limit Switch (Option)



Multi Function Tiller Handle



Tohatsu Onboard Communication System