

FOUR
STROKE

MFS5C



Exceed the European
Union emission standards.



California C.A.R.B.
three star rating
for ultra-low emissions.

FOUR
STROKE

Specifications

Type		Four Stroke
Maximum output	KW (PS)	3.68 (5)
Maximum operating range	r/min	4500-5500
Fuel consumption at W.O.T	L/Hr (gal/Hr)	1.7 (0.45)
Number of cylinder		1
Bore x Stroke	mm (in)	59x45 (2.32x1.77)
Displacement	ml (Cu in)	123 (7.50)
Engine lubrication system		Trochoid pump
Starting system		Manual
Spark plug		NGK DCPR6E
Ignition timing	degree	BTDC0°- BTDC25°
Alternator output		(Option 12V 60W 5A)
Engine oil		4-Stroke Engine Oil
Engine oil capacity	L (qt)	0.45 (0.47)
Fuel tank capacity	L (gal)	1.15 (0.3) Integral tank (only S/L) 12 (3.17) Separate tank (only SS/SL, S/L optional)
Speed control		Twist grip type
Gear reduction ratio		2.15 (13:28)
Emission Compliance		EU & EPA & CARB 3-Star

FOUR STROKE

Specifications and descriptions are subject to change without notice.

Standard & Optional Equipments

Type	S/L	SS/SL
Electric Starter	-	-
Manual Recoil Starter	●	●
Decompression Release	●	●
Engine Stop Switch Lanyard	●	●
Alternator	○	○
Rectifier	○	○
Dual Tank Connector	15/20	15/20
Transom	●	-
Propeller	●	●
Analog Tachometer	-	-
Analog Trim Meter	-	-
Remote Control Box	-	-
12L (3.1 Gal) Plastic Fuel Tank	○	●
1.15L (0.3 Gal) In-tank	●	-
Tool Kit	●	●
Emergency Starter Rope	●	●
Spare Spark Plug	●	●
Owners Manual	●	●

● Standard ○ Optional



1-Cylinder



Alternator (Option)



Charging System (Option)



Thermostat



Built-in Tank



Dual Fuel System (Option)



Throttle Friction



Steering Friction Adjustment (FOR TILLER HANDLE MODEL)



High Solid Paint Coating



Light Weight



Front Shift Control

FOUR STROKE