

FOUR  
STROKE

MFS6C



Exceed the European  
Union emission standards.



California C.A.R.B.  
three star rating  
for ultra-low emissions.

FOUR  
STROKE

## Specifications

<b>Type</b>		Four Stroke
<b>Maximum output</b>	KW (PS)	4.4 (6)
<b>Maximum operating range</b>	r/min	5000-6000
<b>Fuel consumption at W.O.T</b>	L/Hr (gal/Hr)	2.0 (0.53)
<b>Number of cylinder</b>		1
<b>Bore x Stroke</b>	mm (in)	59x45 (2.32x1.77)
<b>Displacement</b>	ml (Cu in)	123 (7.50)
<b>Engine lubrication system</b>		Trochoid pump
<b>Starting system</b>		Manual
<b>Spark plug</b>		NGK DCPR6E
<b>Ignition timing</b>	degree	BTDC0°- BTDC25°
<b>Alternator output</b>		(Option 12V 60W 5A)
<b>Engine oil</b>		4-Stroke Engine Oil
<b>Engine oil capacity</b>	L (qt)	0.45 (0.47)
<b>Fuel tank capacity</b>	L (gal)	12 (3.17)
<b>Speed control</b>		Twist grip type
<b>Gear reduction ratio</b>		2.15 (13:28)
<b>Emission Compliance</b>		EU & EPA & CARB 3-Star

FOUR STROKE

Specifications and descriptions are subject to change without notice.

## Standard & Optional Equipments

Type	S/L
Electric Starter	-
Manual Recoil Starter	●
Decompression Release	●
Engine Stop Switch Lanyard	●
Alternator	○
Rectifier	○
Transom	15/20
Propeller	●
Analog Tachometer	-
Analog Trim Meter	-
Remote Control Box	-
12L (3.1 Gal) Plastic Fuel Tank	●
Tool Kit	●
Emergency Starter Rope	●
Spare Spark Plug	●
Owners Manual	●

● Standard ○ Optional

FOUR STROKE



**1-Cylinder**



**Alternator (Option)**



**Charging System (Option)**



**Thermostat**



**Throttle Friction**



**Steering Friction Adjustment (FOR TILLER HANDLE MODEL)**



**High Solid Paint Coating**



**Light Weight**



**Front Shift Control**