

TLDI

MD90C₂



Exceed the European Union emission standards.



California C.A.R.B.
three star rating
for ultra-low emissions.

TLDI

Specifications

Type TLDI (Two-Stroke Low-Pressure Direct Fuel Injection)

Maximum output KW (PS) 66.2 (90)

Maximum operating range r/min 5150-5850

Fuel consumption at W.O.T L/Hr (gal/Hr) 30 (7.9)

Number of cylinder 3

Bore x Stroke mm (in) 86x72.7 (3.39x2.86)

Displacement ml (Cu in) 1267 (77.3)

Engine lubrication system Auto Mixing (Electrical oil

Starting system pump) Electric starter

Spark plug NGK IZFR6Q

Ignition timing Electronically advanced

Alternator output 12V 490W 40A

Engine oil 2-Stroke Engine Oil

Volume of engine oil L (gal) 4 (1.06)

Fuel tank capacity L (gal) Option 25 (6.6)

Speed control Remote control

Gear reduction ratio 2.33 (13:28)

Emission Compliance EU & EPA & CARB 3-Star

Specifications and descriptions are subject to change without notice.

TLDI

Standard & Optional Equipments

Type	EPTOL/UL
Electric Starter	●
Engine Stop Switch Lanyard	● *
Alternator	●
Rectifier	●
Power Trim & Tilt	●
Oil Auto Mixing	●
Transom	20/25
Propeller	○
Analog Tachometer	○
Analog Trim Meter	○
Remote Control Box	○
25L (6.6 Gal) Plastic Fuel Tank	○
Tool Kit	●
Spare Spark Plug	●
Owners Manual	●

● Standard ○ Optional

* Equipped with the remote control box



3-Cylinder



Direct Fuel Injection



Low Fuel Consumption



Alternator



Charging System



Thermostat



Trolling Speed Control



Power Trim & Tilt



Multifunctional Tachometer



Over-Heat Buzzer



High Solid Paint Coating



Tohatsu Onboard Communication System

TLDI