## TLDI MD50B2



## **Specifications**

Туре	TLDI (Two-Strok	ke Low-Pressure Direct Fuel Injection)
Maximum output	KW (PS)	36.8 (50)
Maximum operating	g range r/min	5150-5850
Fuel consumption at	W.O.T L/Hr (gal/Hr)	16.5 (4.4)
Number of cylinder		3
Bore x Stroke	mm (in)	68x64 (2.68x2.52)
Displacement	ml (Cu in)	697 (42.53)
Engine lubrication s	ystem	Auto Mixing (Mechanical oil pump)
Starting system		Electric starter
Spark plug		NGK IZFR6Q
Ignition timing		Electronically advanced
Alternator output		12V 280W 23A
Engine oil		2-Stroke Engine Oil
Volume of engine of	<b>il</b> L (gal)	2 (0.53)
Fuel tank capacity	L (gal)	25 (6.6)
Speed control		Twist grip type, Multi Function Tiller Handle or Remote Control
Gear reduction ratio	0	1.85 (13:24)
Emission Compliance	ee	EU & EPA & CARB 3-Star

Specifications and descriptions are subject to change without notice.

Standard & Optional Equipments				
Туре	EPTOS/L			
Electric Starter	•			
Engine Stop Switch Lanyard	•*			
Alternator	•			
Rectifier	•			
Power Trim & Tilt	•			
Oil Auto Mixing	•			
Transom	15/20			
Propeller	•			
Analog Tachometer	•			
Analog Trim Meter	•			
Remote Control Box	•			
Multi Tiller Handle	0			
25L (6.6 Gal) Plastic Fuel Tank	•			
Tool Kit	•			
<b>Emergency Starter Rope</b>	•			
Spare Spark Plug	•			
Owners Manual	•			

- Standard O OptionalEquipped with the remote control box



3-Cylinder



**Direct Fuel** Injection



Low Fuel Consumption



Alternator



**Charging System** 



Thermostat



Trolling Speed Control



Throttle Friction Adjust



Power Trim & Tilt



Multifunctional **Tachometer** 



**Over-Heat Buzzer** 



High Solid Paint Coating



**Dual Water** Intake



**Multi FunctionTiller** Handle #014213AB and later models



**Tohatsu Onboard Communication System**